

# Premium Resin-Enhanced Wax

## RIBBON PROPERTIES

Ink Color	Black
Base Film Thickness	4.5 ± 0.3 μ
Ink Thickness	3.2 ± 0.2 μ
Total Thickness	7.7 ± 0.5 μ
Transfer Temperature	150°F / 66°C

## RECOMMENDED SUBSTRATES

TAG / PAPER	SYNTHETICS	SPECIALTY MATERIAL
Uncoated Tag	Polypropylene	Tyvek®
Coated Tag	Polyethylene	Tyvek Brillion®
Coated Face Sheets	Polyolefin	Valeron®
Uncoated Face Sheets	Vinyl (Topcoat)	
Gloss Sheets		

## RECOMMENDED APPLICATIONS

<b>AUTOMOTIVE</b> 	<b>ELECTRONICS</b> 	<b>FOOD &amp; BEVERAGE</b> 	<b>HEALTH &amp; BEAUTY</b> 	<b>INVENTORY &amp; LOGISTICS</b> 
<b>OUTDOOR</b> 	<b>PHARMACEUTICAL</b> 	<b>RETAIL</b> 		

## UL / cUL LABELING REFERENCES

FLEXcon: PGJ12.MH16635

## PRODUCT FEATURES

### Versatility Defined

Works on nearly anything

### Sharp

Superior small character clarity

### Durable

Abrasion resistant

## PLUS:

- Reduced Print Energy
- Smoothcoat® Backcoat
- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant
- Halogen-free

Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.