

# Signature Series Wax-Resin

## RIBBON PROPERTIES

Ink Color	Black
Base Film Thickness	4.8 ± 0.3 μ
Ink Thickness	3.1 ± 0.2 μ
Total Thickness	7.9 ± 0.5 μ
Transfer Temperature	181°F / 83°C

## RECOMMENDED SUBSTRATES

TAG / PAPER	SYNTHETICS	SPECIALTY MATERIAL
Uncoated Tag	Polypropylene	Tyvek®
Coated Tag	Polyethylene	Tyvek Brillion®
Coated Face Sheets	Polyolefin	Valeron®
Uncoated Face Sheets	Polystyrene	V-max®
Gloss Sheets	Vinyl (Topcoat)	

## RECOMMENDED APPLICATIONS

### AUTOMOTIVE



### COMPLIANCE



### HEALTH & BEAUTY



### INVENTORY & LOGISTICS



### OUTDOOR



### RETAIL



## PRODUCT FEATURES

### ✓ Versatility Defined

Works on nearly anything

### ✓ Sharp

Superior small character clarity

### ✓ Durable

Abrasion resistant

## PLUS:

- Reduced Print Energy
- Smoothcoat® Backcoat
- FDA Indirect Food Contact
- REACH Compliant
- RoHS Compliant
- Halogen-free

Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.